

Applications:

- ☐ Pharmaceutical/Clean Rooms
- ☐ Food Processing/Restaurants
- ☐ Water Treatment Plants
- ☐ Transportation/Transit

STC: STC 35-51 (Consult Factory)



Fire Rating: Up to and including 3 Hours

Warranty: See “Warranty” Statement for More Details
One Year (365 days) from the date of delivery

Material Types:

- ☐ Alloy 304
- ☐ Alloy 304L
- ☐ Alloy 316
- ☐ Alloy 316L

Finishes: (See Stainless Steel Finishes Tech Sheet)

- ☐ #4 Brushed (Standard)
- ☐ #2B Mill / Paint Grade
- ☐ #6 Satin
- ☐ #8 Mirror Polished
- ☐ Long Grain
- ☐ Non-Directional / Angel Hair
- ☐ Bead Blast
- ☐ Random Swirl

Face Skin Options:

- ☐ 18 Gauge (0.042 min) – ANSI A250.8 Level 2
- ☐ 16 Gauge (0.053 min) – ANSI A250.8 Level 3
- ☐ 14 Gauge (0.067 min) – ANSI A250.8 Level 4

Core:

- ☐ Polystyrene (Standard)
- ☐ Polyurethane
- ☐ Steel Stiffened
- ☐ Temperature Rise Core
- ☐ Lead Lined
- ☐ Bullet Resistant (Consult Factory)

Size: Consult Factory

- ☐ Actual Size:
 - o Actual Width = Nominal Width – 1/4"
 - o Actual Height = Nominal Height – 1/8" (top) – Undercut

Elevations:

- ☐ Flush
- ☐ Stile & Rail
- ☐ Embossed
- ☐ Dutch Doors
- ☐ Glazing Trims / Light Kits
- ☐ Channel Stop Trim / Integral Light Kits

Edge Type:

- ☐ Bevel Hinge & Bevel Lock – 1/8" over 2" (Standard)
- ☐ Square Hinge & Bevel Lock (Standard for Cont. Hinge)
- ☐ Square Hinge & Square Lock (optional)

Edge Seam:

- ☐ Open Seam (Lock Seam) – ANSI A250.8 Model 1
- ☐ Seamless Continuous Welded – ANSI A250.8 Model 2

Top & Bottom Channels:

- ☐ 18 Gauge (0.042 min), Projection Welded to Face Skins
- ☐ Inverted (standard)
- ☐ Flush (optional)

These are the more common finishes used in the architectural building industry. For additional options please contact the factory.



#4 Satin Brushed Finish (Standard)



#2B Mill Finish (Paint Grade)



#6 Satin Finish



#8 Mirror Polished Finish



Long Grain Finish



Non-Directional Finish (Angel Hair)



Bead Blast Finish



Random Swirl Finish